FOR REFERENCE ONLY, NOT TO BE USED TO BUILD A TRAILER



Excerpted from "Popular Home Craft" March-April 1939

For reference only

Built With Dimes; Total Cost \$60



Note tiny proportions compared to modern car. The exterior is varnished.

# "HONEYMOON HOUSE TRAILER"

HIS trim little trailer, designed and built by Louis Rogers of Pasadena for his wedding trip, has proved its practicability in long service on the road. Mr. Rogers pursued a unique method of saving the money for the material. Each time he changed a dollar bill he put any dimes received into a small bank, so that the trailer literally was built with dimes. Total cost for material was slightly over sixty dollars, and this modest investment was the result of many trips to various junk and wrecking yards. pieces were picked up here and there, and the prospective builder of one like it should bear in mind that he need not use identical material if something different serves the purpose just as well. For instance, a tee-beam is used for the tow bar on the original, but an I-beam, or even a heavy timber can be used instead.

FOR REFERENCE ONLY, NOT TO BE USED TO BUILD A TRAILER

A Chevrolet front axle with 28 in. wheels was used in the Rogers trailer, the tie-rod being cut and bolted to the axle, as in Fig. 1. It is important that the wheels are properly aligned before drilling holes for the bolts. If you are equipped for the job, the ends of the tie-rod may be welded in place. Chassis frame is of pine two-by-fours with angle plates in the corners, secured with bolts. A cross member 18 in, back of the

BY HI SIBLEY

Built With Dimes; Total Cost \$60

front end carries one end of the tow the tow bar. Any standard trailer bar, and a "wishbone" of 1" tubing hitch is satisfactory for this job, and reinforces the former in the manner the chain required by some states illustrated. Sturdy strap iron x- can be secured to one of the bolts braces give rigidity to the frame.

iron farm implement wheel is used quire cutting into the body. in this case; any other wheel of Note that two wing nuts are un-

through the tow bar and two-by-A caster-wheel bracket for sup- four. Note that the wheels are set porting the tow bar when not at- pretty well aft, making for smooth tached to the car is made of flat bar towing. Chevrolet 1926 fenders are iron as illustrated in Fig. 2. A 6" installed, as this type does not refloor plan is just four by eight feet, about this size will be satisfactory. and tongue-and-groove flooring is laid over the chassis frame. Screws screwed to remove the easter from instead of nails should be used




Trailer handles easily and turns in small space.


MARCH-APRIL, 1939

447


FOR REFERENCE ONLY, NOT TO BE USED TO BUILD A TRAILER




Built With Dimes; Total Cost \$60









ceiling beams are notched into the side members as shown. Sides are each cut from a single panel 4 ft. by 8 ft., and are identical. A panel of the same size forms front end and roof, in one piece, and the lid over the kitchenette takes a panel 4 ft. by approximately 4 ft. 3 in. Below this is a removable panel of the same material.

FOR REFERENCE ONLY, NOT TO BE USED TO BUILD A TRAILER

Space for the mattress and springs is 6 ft. 4 in. long, and the bed must be installed before the rear partitions are put in. The partition above the ice box and water tank, however, is so constructed that it can be removed by taking out the screws, in case there is occasion to take out the bed. The joint at corner of roof and side wall is covered with aluminum or other metal moulding, secured with screws, as shown in the sectional drawing.

MARCH-APRIL, 1939

- Incredible as it seems, this tiny trailer has 7'4" space in sleeping compartment, which extends from front end to upright frame member just behind the wheel. Framing is of 3/4" x 11/2" pine. Gussets are used on original, but plans are otherwise.
- Prame work of lid over kitchenette.


  Note 1/4" plywood partitions under low shelf, water tank is installed at left, ice box at right. Louis Rogers, builder, demonstrating.
- View looking aft, before roof is installed. Showing dresser with two side compartments. A mirror is to be set against the middle panel in back.
- Sides and top are sheathed with hard pressed board ½" tempered presdwood. No. 6 oval head screws, ¾", with washers are spaced 5½" apart.

The hinged lid over the kitchenette is shown in detail, Fig. 5. It is hinged at the top with standard butts, and a curved metal strip placed over the joint to keep out the rain. Two iron rods hold the lid up when open, and swing back under when closed. A rack is provided for the table. When in use the latter is supported on two paper-hanger's horses which have been cut down to 28 in. These fold up neatly and are stowed in the bin or compartment above the kitchenette. An automobile door handle with lock is used for the locking device fitted with two bars, as illustrated. There is a light under the lid, and on top, the tail light mounted on a strap iron bracket which also supports the license plate. Below the lid is a removable panel made as shown in Fig. 6. Three dowels in the bottom,

449

Built With Dimes; Total Cost \$60

FOR REFERENCE ONLY, NOT TO BE USED TO BUILD A TRAILER



Built With Dimes; Total Cost \$60

set in holes in the floor, and the up- full width of the trailer, suitable for per end is kept in place by the overlapping moulding of the lid.

Just at the rear end of the door compartments with doors, and a mirror in back. A light is installed above. Note that the bed slides under this dresser, with ample body room between it and the bottom of the dresser to move about.

Dimensions of the kitchenette

curtains, table horses, etc.

The ice box is of galvanized iron insulated with two thicknesses of a dresser is built in, Fig. 7, with two half-inch insulating board, and built into the trailer. Details are down in Fig. 9. The lid is also insulated, and


when closed serves as a workbench for the cook. A 14" copper tube

drains direct to the ground, and a low partition prevents ice from sliding over onto the food adjoining.

It goes without saying that the cover must fit neatly and snugly. As stated before, both doors are


(Continued on page 488)





FOR REFERENCE ONLY, NOT TO BE USED TO BUILD A TRAILER

compartments can be taken from the squared diagram, Fig. 3, and constructional details are shown in Fig. 8. At the bottom left is a built-in water tank, having a faucet that swings up out of the way of the lid when the latter is closed. Two drawers are provided, just to the left of center, and an ice box is built in on the right side. The stove slides out on wooden rails with grooves at right angles, preventing its shaking off when in motion. Above it are two panels sliding in rabbetted guides, and a dish compartment built to accommodate the dishes. The panels have brass finger-sockets to set in, and the guides should be sufficiently wide to prevent binding in damp weather. Give both the guides and edges of the plywood panels a thorough application of wax. In the dish rack, glasses set in holes in a shelf, and rabbeted groves take care of the plates. Above this is a bin the



METAL MOULDING OVER HINGE



Louis Rogers of Pasadena, designer and builder, demonstrates the novel window bracket. Normally, it is worked from the inside.

MARCH-APRIL, 1939

451

Built With Dimes; Total Cost \$60

FOR REFERENCE ONLY, NOT TO BE USED TO BUILD A TRAILER

488



upon the kinds of solvents and diluents which are placed in the lacquers by the manufacturers. Lacquers dry entirely by evaporation of the solvents and diluents which may be varied in order to secure very fast or rather slow drying. Undercoats containing linseed oil especially are not now used under lacquers by experienced finishers. Fillers and varnishes contain linseed oil usually and are not fit for undercoats for lacquers.

#### "HONEYMOON HOUSE TRAILER"

(Continued from page 451)

identical, but one is fitted with a Yale lock, and the other fastened from the inside with an icebox handle taken from an old refrigerator. Construction of the door is shown in Fig. 10 and Mr. Rogers has devised a very ingenious window fastener and bracket combined. This consists simply of a coiled screen-door spring passing through two eyes set at right angles, as in Fig. 10. By pushing the spring out through the eyes it opens the window from the inside and holds it in any position. When closed, the end of the spring is put on a hook at one side, making an effective lock. The spring passes through a hole in the copper screen. The window is hinged at the top with a piano hinge, and the glass is held by a frame made of galvanized sheet iron bent as shown in the sectional drawing, and mitred and soldered at the corners. Painted over brown of the same shade as the sheathing of the trailer, it makes a neat appearance.

Aluminum moulding is placed over the door sill, with a small eavestrough of the same material above the door, as shown in the sectional drawing. In forming these pieces as well as all other sheet metal work it will be necessary, for a neat job, to have your local tinsmith do the work with his shop equipment. It shouldn't cost much.

With a trailer of these compact dimensions, dressing is best done outside, and Mr. Rogers has rigged up a very satisfactory dressing room at the door with a curtain. This is supported on two rods which slide out from the top of the body on either side of the door, Fig. 11, and are just 4' long, the width of the trailer. A third rod, fitted with sockets at each end made of copper tubing, joins the other two and is held up by a wooden pole. Curtains strung along this make a very satisfactory dressing room, especially when a wood floor is provided. This last (see photo) is made of slats something on the order of Venetian blinds and can be rolled up and stowed in small space.

Lighting on Mr. Roger's trailer is from the car battery, but one could be put in the trailer itself independent of the car. There are six bulbs installed, one under the shelf at the forward end of the sleeping compartment, one over the dresser, one under the kitchenette lid, one tail light and two blue clearance lights. A knife switch is provided to throw on current from car battery, or switch over to city 110-v circuit through a transformer.

POPULAR HOMECRAFT